



Distribution box

The easiest way to organize the power distribution cables.

Description

Enclosure made of antistatic material with rounded corners and slots for easy carrying and quick hanging. Sockets are bolted on both sides of the box. Plug and sockets make CEAG.

Specifications

- Box equipped with slots for easy hanging (by S-hooks)
- Available in 230V, 42-48V, 24V or 12V
- Max 16A input
- Input power supply: CEAG plug and flexible cable (H07RNF, 2/3 x 2,5mm²).
- Cable length upon demand.
- Output: 4 pcs matching CEAG sockets.
- Plate material antistatic for use in ATEX zones.



Series 86	Equipped with 4 wall sockets
Dimensions	Approx 520 x 395 x 263mm
Weight	Approx 10 kg
Cable	H07RNF and CEAG plug in accordance with wall sockets
Cable length Lxx	See indication Lxx. Standard 10m.
Wall sockets	230V: GHG5118306R0001
	42V: 2p GHG5425212V0000, 3p GHG5425312V0000
	24V: 2p GHG5425200V0000, 3p GHG5425300V0000
	12V : upon request
Certification gaz	II 2 G Ex d e IIC T4 Gb
Certification dust	II 2 D Ex tb IIIC T80°C Db, IP66
Operational temp.	Tamb -20°C to +40°C
Suitable for zones	1, 2, 21, 22
Part number with 230V sockets	8630320Lxx
Part number with 2p 42V sockets	8630620Lxx
Part number with 3p 42V sockets	8620621Lxx
Part number with 2p 24V sockets	8620720Lxx
Part number with 3p 24V sockets	8620721Lxx
HS code: 85369010, country of origin, the Netherlands.	

6-2025

Data and pictures approx. only and errors and modifications reserved.

Tel.: +31183309333 | atexindustries.com | info@atexindustries.com

Hoogstraat 32, NL- 4285 AH Woudrichem, the Netherlands

Chamber of Commerce reg. 64566110

BANK : ING BANK IBAN NL07INGB 0006 0593 87, BIC: INGBNL2A VAT: NL 855722186 B01, EORI NL855722186